

# **PUTNAM COUNTY, WEST VIRGINIA FLOODPLAIN ORDINANCE**

AN ORDINANCE ESTABLISHING A FLOODPLAIN AREA AND REQUIRING ALL CONTRACTORS, PERSONS, PARTNERSHIPS, BUSINESSES, AND CORPORATIONS TO OBTAIN A PERMIT FOR DEVELOPMENT AND THE CONSTRUCTION, SUBSTANTIAL IMPROVEMENT, OR RELOCATION OF ANY BUILDING OR STRUCTURE; PROVIDING FOR CERTAIN MINIMUM STANDARDS FOR CONSTRUCTION WITHIN THE FLOODPLAIN AREA AND SETTING FORTH SPECIAL PROCEDURES FOR SUBMISSION AND APPROVAL OF PLANS; AND ESTABLISHING PENALTIES FOR ANY PERSON WHO FAILS TO COMPLY WITH THE REQUIREMENTS OR PROVISIONS OF THIS ORDINANCE.

BE IT ENACTED AND ORDAINED by the Putnam County Commission, as follows:

## **ARTICLE I - GENERAL PROVISIONS**

### **Section 1 Authority**

- A. The provisions of this ordinance have been prepared with the intention of meeting the requirements of THE NATIONAL FLOOD INSURANCE ACT OF 1968 (42 U.S.C. 4001 et seq.) AMENDED BY THE CONGRESS OF THE UNITED STATES THROUGH THE 15<sup>th</sup> OF FEBRUARY, 1975 (PUBLIC LAW 91-152),
- B. Authority to adopt, administer and enforce this ordinance is vested in the community pursuant to WEST VIRGINIA STATE CODES 8-12-14, 7-1-3n, 7-1-3v and 7-1-3kk.

### **Section 1.1 Intent**

The intent of this ordinance is to:

- A. Promote the general health, welfare, and safety of the community.
- B. Encourage the utilization of appropriate construction practices in order to prevent or minimize flood damage in the future.
- C. Minimize danger to public health and safety by protecting water supply and sanitary sewage disposal in cooperation with the County Sanitarian, and to protect natural drainage.
- D. Assure the County Assessor obtains information concerning improvement of real property as required by WV State Code 11-3-3A.
- E. Assure County E-911 addresses are obtained to maintain the currency of established emergency response dispatch systems.

- F. Reduce financial burdens imposed on the community, its governmental units, and its residents, by preventing the unwise design and construction of development in areas subject to flooding.

#### Section 1.2 Abrogation and Greater Restrictions

This ordinance supersedes any ordinance currently in effect in flood prone areas. Any ordinance, however, shall remain in full force and effect to the extent that its provisions are more restrictive.

#### Section 1.3 Applicability

It shall be unlawful for any contractor, person, partnership, business, or corporation to undertake or cause to be undertaken, any development, new construction, substantial improvement, repair of substantial damage, or the placement or relocation of any structure (including manufactured homes) within Putnam County, unless a permit application has been completed and a permit or certificate of compliance has been obtained from the Floodplain Administrator. In addition, where land partially or fully in the floodplain is to be developed, subdivided, utilized for a manufactured home park or subdivision or otherwise developed, a site plan with elevation data must be submitted to, and approved by, the Floodplain Administrator prior to any development.

Provision of all other codes, ordinances, and regulations shall be applicable insofar as they are consistent with the provisions of this ordinance and the community's need to minimize the hazards and damage resulting from flooding.

#### Section 1.4 Matters not provided for specifically

Where conditions are encountered that are not specifically provided for herein, the floodplain administrator shall determine the applicability of the provisions of this ordinance in accordance with its intent, and shall require the applicant to take appropriate measures pursuant to such determination.

### **ARTICLE II - INTERPRETATIONS AND DEFINITIONS**

#### Section 2.1 Interpretations

A. For the purpose of this ordinance, the following interpretations shall apply:

1. Words used in the present tense include the future tense
2. The singular includes the plural.
3. The plural includes the singular.
4. The Term "shall" or "will" is always mandatory.
5. The word "building" or "structure" shall be construed as if followed by the phrase "or part thereof".

6. The word “Ordinance” shall refer to the Floodplain Ordinance.

## Section 2.2 Definitions

### General

Unless specifically defined below, words and phrases used in this ordinance shall be interpreted so as to give this ordinance its most reasonable application.

### Appurtenant Structure

A structure on the same parcel of property as the principal structure and the use of which is incidental to the use of the principal structure. This does not include a gas or liquid storage tank.

### Base Flood

The flood, which has been selected to serve as the basis upon which the floodplain management provisions of this and other ordinances have been prepared; for purposes of this ordinance, the one-hundred (100) year flood.

### Base Flood Elevation (BFE)

The water surface elevation of the base flood in relation to the datum specified on the community’s Flood Insurance Rate Map. For the purposes of this ordinance, the one hundred (100) year flood or 1% annual chance flood.

### Basement

Any area of the building having its floor sub grade (below ground level) on all sides.

### Certificate of Compliance

A certification that the entire development, including the elevation of fill or the lowest floor of a structure is in compliance with all of the provisions of this ordinance.

### Contractor - WV State Code 21-11-3(c)

A person who in any capacity for compensation, other than as an employee of another, undertakes, offers to undertake, purports to have the capacity to undertake, or submits a bid to construct, alter, repair, add to, subtract from, improve, move, wreck or demolish any building, highway, road, railroad, structure or excavation associated with a project, development or improvement, or to do any part thereof, including the erection of scaffolding or other structures or works in connection therewith, where the cost of the undertaking is one thousand dollars or more. Contractor includes a construction manager who performs management and counseling services on a construction project for a professional fee.

Contractor does not include:

(1) One who merely furnishes materials or supplies without fabricating or consuming them in the construction project.

(2) A person who personally performs construction work on the site of real property which the person owns or leases whether for commercial or residential purposes;

(3) A person who is licensed or registered as a professional and who functions under the control of any other licensing or regulatory board, whose primary business is real estate sales, appraisal, development, management and maintenance, who acting in his or her respective professional capacity and any employee of such professional, acting in the course of his or her employment, performs any work which may be considered to be performing contracting work.

(4) A pest control operator licensed under the provisions of section seven, article sixteen-a, chapter nineteen of this code to engage in the application of pesticides for hire, unless the operator also performs structural repairs exceeding one thousand dollars on property treated for insect pests; or

(5) A corporation, partnership or sole proprietorship whose primary purpose is to prepare construction plans and specifications used by the contractors defined in this section and who employs full time a registered architect licensed to practice in this state or a registered professional engineer licensed to practice in this state. Contractor also does not include employees of such corporation, partnership or sole proprietorship.

### Development

Any man-made change to improved or unimproved real estate, including but not limited to buildings or other structures, mining, dredging, filling, grading, paving, excavation or drilling operations or storage of equipment or materials.

### Flood

A general and temporary inundation of normally dry land areas.

### Flood Insurance Rate Map (FIRM)

The official map on which the Federal Emergency Management Agency has delineated both the special flood hazard areas and the risk premium zones applicable to the community. A FIRM that has been made available digitally is called a Digital Flood Insurance Rate Map (DFIRM).

### Flood Insurance Study

The official report in which the Federal Emergency Management Agency has provided flood profiles, floodway information, and water surface elevations.

## Floodplain

- (1) A relatively flat or low land area adjoining a river, stream, or watercourse which is subject to partial or complete inundation;
- (2) An area subject to the unusual and rapid accumulation or runoff of surface waters from any source.

## Floodplain Administrator

The Putnam County Planning Commission Director shall be the Floodplain Administrator. The Planning Commission Director may delegate this authority to others as deemed appropriate. The Floodplain Administrator may also be identified as the Floodplain Manager.

## Floodway

The channel of a river or other watercourse and the adjacent land area that must be reserved to discharge the base flood without increasing the water surface elevation of that flood more than one foot at any point.

## Flood proofing

Any combination of structural and non-structural additions, changes or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures and their contents.

## Freeboard

A factor of safety usually expressed in feet above a flood level for purposes of floodplain management. Freeboard tends to compensate for unknown factors that may contribute uncertainty to flood heights of any given flood and floodway condition, such as wave action, blockage at stream crossings, and increased runoff from urbanization of the watershed.

## Highest Adjacent Grade (HAG)

The highest natural elevation of the ground surface immediately adjacent to the development or structure foundation. This is primarily used during insurance rating in approximated floodplains.

## Historic Structure

Any structure that is:

- (a) Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
- (b) Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic

district or a district preliminarily determined by the Secretary to qualify as a registered historic district

- (c) Individually listed on a state inventory of historic places in states with historic preservation programs which have been approved by the Secretary of the Interior; or,
- (d) Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either:
  - (i) By an approved state program as determined by the Secretary of the Interior; or,
  - (ii) Directly by the Secretary of Interior in states without approved programs.

#### Licensed Manufactured Home Dealer

A business licensed to sell Manufactured Homes in the state of WV as set forth in the WV state code.

#### Licensed Manufactured Home Installer

A contractor licensed to install Manufactured Homes in WV as set forth in the WV State Code.

#### Licensed Professional Surveyor

Any person licensed by the WV state board of examiners of land surveyors to engage in the practice of land surveying as defined in WV state code.

#### Lowest Floor

The lowest floor of the lowest enclosed area (including basement). An unfinished enclosure constructed with flood resistant materials as defined in the FEMA Technical Bulletin 2-93 (FIA-TB-2) and usable solely for parking of vehicles, building access or storage in an area other than a basement area is not considered a building's lowest floor; Provided, that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements of this ordinance.

#### Manufactured Home

A structure, transportable in one or more sections, which is built on a permanent chassis and is designed for use with or without a permanent foundation when connected to the required utilities. The term "manufactured home" does not include a "recreational vehicle".

### New Construction

Structures for which the Start of Construction as herein defined commenced on or after August 17, 1987 and including any subsequent improvements to such structures. Any construction started after effective date of the community's first floodplain ordinance adopted by the community and before the effective start date of this floodplain ordinance is subject to the ordinance in effect at the time the ordinance was issued, provided the start of construction was within 180 days of permit issuance.

### One-Hundred (100) Year Flood

A flood that has one chance in one-hundred or a one percent chance of being equaled or exceeded in any given year.

### Practice of Engineering

Any service or creative work, as described in WV State Code Article 13, the adequate performance of which requires engineering education, training and experience in the application of special knowledge of the mathematical, physical and engineering sciences to such services or creative work as consultation, investigation, evaluation, planning and design of engineering works and systems; planning the use of land and water; teaching of advanced engineering subjects, engineering surveys and studies; and the review of construction for the purpose of assuring compliance with drawings and specifications any of which embraces such services or work, either public or private, in connection with any utilities, structures, buildings, machines, equipment, processes, work systems, projects and industrial or consumer products or equipment of a mechanical, electrical, hydraulic, pneumatic or thermal nature, insofar as they involve safeguarding life, health or property, and including such other professional services as may be necessary to the planning, progress and completion of any engineering services. Engineering surveys include all survey activities required to support the sound conception, planning, design, construction, maintenance and operation of engineered projects.

Any person who practices any branch of the profession of engineering or who, by verbal claim, sign, advertisement, letterhead, card or in any other way represents himself or herself to be a registered professional engineer, or by using another title implies that he or she is a registered professional engineer or that he or she is registered under WV State Code, Article 13 or who holds himself or herself out as able to perform, or who performs any engineering service or work or any other service designated by the practitioner which is recognized as engineering, is considered to practice or offer to practice engineering within the meaning and intent of WV State Code, Article 13.

### Person

Any individual or group of individuals, corporation, partnership, association or other entity, including State and local governments and agencies.

### Principally Above Ground

Where at least 51 percent of the actual cash value of a structure, less land value, is above ground.

### Recreational Vehicle

A vehicle which is:

- (a) built on a single chassis; (b) 400 square feet or less when measured at the largest horizontal projection; (c) designed to be self-propelled or permanently towable by a light duty truck; and (d) designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.

### Registered Professional Engineer

A person who has been duly registered or licensed as a registered professional engineer by the West Virginia state board of registration for professional engineers as required under WV State Code, Article 13 et seq.

### Remedy a Violation

To bring a structure or other development into compliance with the requirements of this ordinance, or, if full compliance is not possible, to reduce the adverse impacts of the non-compliance to the greatest extent feasible.

### Reasonably Safe from Flooding

Means base flood waters will not inundate the land or damage structures to be removed from the special flood hazard area and that any subsurface waters related to the base flood will not damage existing or proposed buildings.

### Special Flood Hazard Area

The land in the floodplain subject to a one percent or greater chance of flooding in any given year. Special flood hazard areas are designated by the Federal Emergency Management Agency in Flood Insurance Studies and on Flood Insurance Rate Maps as Zones A, AE, AO, A1-30, and A99. This term shall also include areas shown on other flood hazard maps that are specifically listed or otherwise described in this ordinance.

Start of Construction *(The definition for start of construction is to be used only when calculating the starting time for expiration of a permit.)*

The date the permit was issued, including permits for substantial improvement or repair of substantial damage, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond initial excavation, or the placement of a manufactured home on a



foundation. Although a permit must be obtained prior to beginning, permanent construction does not include land preparation, such as clearing, grading and filling, nor does it include the installation of streets and/or walkways, nor does it include excavation for a basement, footings, piers or foundations or the erection of temporary forms, nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For an alteration, the actual start of construction means the first alteration of any wall, ceiling, floor or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

### State Coordinating Office

The West Virginia Division of Homeland Security and Emergency Management

### Stream

As defined in WV State Code 7-1-3U, any watercourse, whether natural or man-made, distinguishable by banks and a bed, regardless of their size, through which water flows continually or intermittently, regardless of its volume.

### Structure

A walled and roofed building, including a gas or liquid storage tank that is principally above ground, as well as a manufactured home.

### Substantial Damage

Damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damage condition would equal or exceed 50 percent of the market value of the structure before the damage occurred. Substantial damage also means cumulative flood-related damages sustained by a structure on two separate occasions during a 10 year period for which the cost of repairs at the time of each flood event equals or exceeds 25 percent of the market value of the structure before the damage occurred. See “Substantial Improvement.”

### Substantial Improvement

Any repair, reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure before the Start of Construction of the improvement.

This term includes structures, which have incurred “substantial damage”, as defined herein regardless of the actual repair work performed. The term does not, however, include any project for improvement of a structure to correct existing violation of state or local health, sanitary or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions.

Historic structures undergoing repair or rehabilitation that would constitute a substantial improvement as defined above, must comply with all ordinance requirements that do not preclude the structure’s continued designation as a

historic structure. Documentation that a specific ordinance requirement will cause removal of the structure from the National Register of Historic Places or the State Inventory of Historic places must be obtained from the Secretary of the Interior or the State Historic Preservation Officer. Any exemption from ordinance requirements will be the minimum necessary to preserve the historic character and design of the structure.

For the purpose of this definition improvement is considered to occur when the first alteration of any wall, ceiling, floor or other structural part of the building commences whether or not that alteration affects the external dimensions of the structure.

#### Top of Bank

The lines depicted on the FIRM maps delineating each side of a stream indicate the top of bank. In the field a professional familiar with fluvial geomorphology should document the top of bank. When a professional is not employed the top of the bank will be considered to be the top of the first significant slope landward of the waters edge when it is followed by at least 50 feet of relatively flat land.

#### Violation

The failure of any structure or development to be fully compliant with all requirements of this ordinance. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required by this ordinance is presumed to be in violation until such time as that documentation is provided.

### **ARTICLE III - ESTABLISHMENT OF THE FLOODPLAIN AREA**

#### Section 3.1 Identification

- A. The identified floodplain area shall be those areas of unincorporated Putnam County, West Virginia which are subject to the one hundred (100) year flood, as shown on the Flood Insurance Rate Map (FIRM) and described in the Flood Insurance Study (FIS) prepared for Putnam County, West Virginia by the Federal Emergency Management Agency (FEMA) dated February 2, 2012 or the most recent revision thereof.
- B. The identified floodplain area shall also be those areas of unincorporated Putnam County, West Virginia which have been identified as flood hazard areas by the Putnam County Planning Commission by use of historic or other technical data and shown on the Putnam County "Local Flood Hazards Map". These areas shall be designated as appropriate with the level of technical data described below and shall be managed accordingly.

#### Section 3.2 Descriptions of Floodplain Areas

The identified floodplain shall consist of the following four specific areas:

- A. The Floodway area (F1) shall be those areas identified as such in the FIS and as shown on the floodway map or FIRM. The term shall also include

floodway areas identified in other studies for the approximated area discussed in Section D Below.

- B. The Floodway Fringe area (F2) shall be those areas for which specific one hundred (100) year flood elevations have been provided in the FIS but which lie beyond the floodway area.
- C. The AE Area without Floodway (F3) shall be those areas identified as an AE Zone on the FIRM included in the FIS prepared by FEMA for which 100-year flood elevations have been provided but no Floodway has been delineated.
- D. The Approximated area (F4) shall be those areas identified as an A Zone on the FIRM or floodway map included in the FIS prepared by FEMA and for which no one hundred (100) year flood elevations have been provided. For these areas, elevation and floodway information from other Federal, State, or other acceptable source shall be used when available. Where other acceptable information is not available the Floodplain Administrator shall require the applicant to determine the elevation with hydrologic and hydraulic engineering or other techniques. When hydrologic and hydraulic analyses are required, they shall only be undertaken by a registered professional engineer who shall certify that the methods used correctly reflect currently accepted technical concepts. The resultant study shall include a cover letter, signed by the responsible professional, providing a statement of findings in basic terms. In addition, studies, analyses, computations, etc. shall be submitted in sufficient detail to allow a thorough technical review by the floodplain administrator.

### Section 3.3 Changes in Designation of Area

- A. The delineation of the identified floodplain area may be revised by the Putnam County Planning Commission where natural or man-made changes have occurred and/or more detailed studies conducted or undertaken by the U.S. Army Corps of Engineers, a River Basin Commission or other qualified agency or individual document the necessity for such changes. However, prior to any such change, approval must be obtained from the Federal Insurance Administration (FIA).
- B. A community's base flood elevations may increase or decrease resulting from physical changes affecting flooding conditions. As soon as practicable, but not later than six months after the date such information becomes available, the community shall notify the NFIP Administrator of the changes by submitting technical or scientific data.
- C. The Putnam County Planning Commission may identify and regulate new flood hazard or ponding areas. These areas may be delineated using locally derived technical information such as flood of record, historic high water marks and/or topographic data.

### Section 3.4 Elevations Prevail

- A. If the structure location appears to be inside the SFHA on the FEMA FIRM's and If the lowest natural grade adjacent to proposed development within an identified flood hazard area is at or above the Base Flood Elevation specified in the Flood Insurance Study (FIS), the structure shall not be required to conform to the flood prevention design and construction standards or flood-related development codes in Article VI. Topographic data certified by a registered professional engineer or licensed professional surveyor shall be submitted in sufficient detail to allow a thorough review by the Floodplain Administrator. The applicant shall apply for a Letter of Map Amendment (LOMA) from FEMA and the determination given to the floodplain administrator within 90 days of issuance of the permit having the Special Flood Hazard Area designation removed from the parcel or structure prior to certificate of occupancy/compliance.
- B. If the lowest natural grade adjacent to proposed development is below the Base Flood Elevation specified in the Flood Insurance Study, the site shall be considered to be within the floodplain area and the proposed structure shall be required to conform to all appropriate provisions of this ordinance.

### Section 3.5 Boundary Disputes

Should a dispute concerning any district boundary arise, an initial determination shall be made by the Floodplain Administrator and any party aggrieved by this decision may appeal to the Putnam County Planning Commission. The burden of proof shall be on the appellant/applicant.

## **ARTICLE IV - UTILIZATION OF THE FLOODPLAIN AREA**

### Section 4.1 Floodway (F1)

- A. Within any floodway area (F1), no encroachments, including fill, new construction, substantial improvements, repair of substantial damage, or other development shall be permitted unless it has been demonstrated through hydrologic and hydraulic analysis performed in accordance with standard engineering practice that the proposed encroachment will not result in any increase in the Base Flood Elevation.
- B. Because floodways present increased risk to human life and property due to their relatively faster and deeper flowing waters the Floodway shall be preserved to the greatest extent possible.
  - 1. New development shall not be permitted in the floodway where reasonable alternatives exist elsewhere. In addition to the requirements below, the applicant shall demonstrate that there are no reasonable alternatives other than the floodway encroachment before a permit is issued.
  - 2. When the floodway is the only reasonable alternative, the applicant shall demonstrate that the floodway encroachment is the minimum necessary to accomplish the project.

3. All permitted uses, activities, and development shall be undertaken in strict compliance with the flood proofing and related provisions contained herein, and in all other applicable codes, ordinances and regulations.
4. In special flood hazard areas for which no regulatory floodway has been designated, the regulatory floodway for small, single lot development not incorporating significant amounts of fill can, at the discretion of the community, be determined to be the channel of the stream and the adjacent land areas to a distance of one-half the width of the special flood hazard area as measured from the top of the bank nearest the site to the upland limit of the 1% annual chance special flood hazard area boundary.

#### Section 4.2 Floodway Fringe (F2) and Approximated Floodplain (F4)

A. In the Floodway Fringe (F2) and Approximated Floodplain (F4), any development and/or use of land shall be permitted provided that all such uses, activities and/or development shall be undertaken in strict compliance with the flood-proofing and related provisions contained herein and in all other applicable codes, ordinances and regulations.

1. In the Approximated Floodplain (F4) the Floodplain Manager shall review, or shall cause to be reviewed, all proposed development not covered by sub-section B below to ascertain the amount being invested and the specific flood risk at the building site and assign a “minimal, moderate or significant” risk level.
  - a. Development determined to represent a minimal risk and costing less than \$10,000 shall be required to provide “Point on Boundary” elevation data and historic flood heights. The Floodplain Manager shall attempt to determine a height that will be reasonably safe from flooding using this elevation data. The Floodplain Manager shall enter the flood height in Section “G” of the Elevation Certificate. Any new or substantially improved structures permitted using this method (other than appurtenant structures) shall be required to have the lowest floor elevated at least three (3) feet above the highest adjacent grade even if the “point on boundary” or historic flood height data would indicate a lower flood elevation. If this method is not adequate to allow the Floodplain Manager to confidently determine the flood height or if the applicant is not satisfied with the height determined the applicant shall be required to utilize one of the alternate methods set forth below.
  - b. Development determined to represent a low to moderate risk and/or costing less than \$150,000 shall provide a Quick-2 engineering program or obtain free LOMA data from FEMA. This semi-detailed method will be used by the Floodplain Manager to determine a “Community Flood Elevation”. The Floodplain Manager shall enter the “Community Flood Elevation” in Section “G” of the Elevation Certificate.

- c. Development determined to represent a high risk and/or costing more than \$150,000` shall develop a Base Flood Elevation using a detailed method such as HEC-ras. This data shall be prepared and certified by a registered professional engineer, who shall certify that the methods used correctly reflect currently accepted technical concepts. The resultant study shall include a cover letter, signed by the responsible professional, providing a statement of findings in basic terms and a completed Elevation Certificate. In addition, studies, analyses, computations, etc. shall be submitted in sufficient detail to allow a thorough technical review by the Floodplain Manager. Base Flood Elevations determined using this method can be used to rate flood insurance, typically resulting in a reduced premium.
- B. Proposed new developments and major subdivisions which are proposed to take place either fully or partially within the Approximated Floodplain area (F4) and which are greater than three (3) lots or two (2) acres, whichever is the lesser, shall include base flood elevation data.
1. This data may be available from an authoritative source, such as the U.S. Army Corps of Engineers, U.S. Geological Survey, Natural Resource Conservation Service or state and local water resource department.
  2. If the required data is not available from other sources the applicant shall develop the technical data using detailed methodologies comparable to those contained in a Flood Insurance Study. This data shall be prepared and certified by a registered professional engineer, who shall certify that the methods used correctly reflect currently accepted technical concepts.

#### Section 4.3 AE Area without Floodway (F3)

Within any AE area without floodway, no new construction or development shall be allowed unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the elevation of the 100-year flood more than one (1) foot at any point. This requirement can be satisfied by utilization of the floodway area where determined.

#### Section 4.4 Approximated Floodplain (Zone A)

##### A. Within any Approximated Floodplain:

1. The Floodplain Administrator shall use elevation and floodway information from Federal, State, or other acceptable sources when available to determine the elevation above which development will be reasonably safe from flooding.
2. When data from an acceptable source is not available, the Floodplain Administrator shall review, or shall cause to be reviewed; all proposed development to determine: 1. the amount being invested and, 2. the specific flood risk at the site. The Floodplain Administrator shall then require the applicant to determine the elevation above which the development will be reasonably safe from flooding using elevation data hydrologic and hydraulic

analyses or other techniques. When hydrologic and hydraulic analyses are required, they shall only be undertaken by a Registered Professional Engineer who shall certify that the methods used correctly reflect currently accepted technical concepts. The resultant study shall include a cover letter, signed by the responsible professional, providing a statement of findings in basic terms. In addition, studies, analyses, computations, etc. shall be submitted in sufficient detail to allow a thorough technical review by the Floodplain Administrator.

#### Section 4.5 Alteration or relocation of a stream

- A. Whenever a developer intends to alter or relocate a stream within the Floodplain Area, the developer shall notify in writing, by certified mail, the Putnam County Floodplain Administrator, The State Coordinating Office, and any adjacent communities of all such intended activities prior to the alteration or relocation of the stream. Copies of all required notifications must be submitted to the Federal Insurance Administration. In addition prior to issuing the local permit, the Floodplain Administrator shall require copies of all necessary permits from those governmental agencies from which Federal or State Law requires approval. Contact information for State and Federal permitting authorities as well as addresses for required notification of appropriate County, State & Federal government agencies are contained in the Putnam County Stream Alteration administrative procedures.
- B. The developer shall also assure the Putnam County Planning Commission in writing that the carrying capacity within the altered or relocated portion of the stream will be maintained. The Floodplain Administrator may require the applicant to demonstrate that the altered or relocated portion of stream will provide equal or greater conveyance than the original stream segment. If hydrologic and hydraulic analyses are required, they shall only be undertaken by registered professional engineers, who shall certify that the methods used correctly reflect currently accepted technical concepts. The resultant study shall include a cover letter, signed by the responsible professional, providing a statement of findings in basic terms. In addition, studies, analyses, computations, etc. shall be submitted in sufficient detail to allow a thorough technical review by the floodplain administrator.
- C. Alteration of a stream includes placement of culverts, bridges or other stream crossings and the removal of culverts. The floodplain administrator may require the use of certain “best practice” techniques in the construction of bridges, culverts or stream crossings to prevent damage, loss of stream crossings and localized flooding caused by blockage. These techniques may include, but are not limited to, wing walls, trash grates or requiring openings to be of sufficient size to pass debris and/or anticipated future increases in flood heights.
- D. All new and replacement bridges, culverts and other stream crossings shall adhere to the relevant anchoring requirements contained in this ordinance.
- E. The developer is required to provide the community a legal agreement detailing all scheduled inspections and maintenance to be performed on altered or relocated watercourses including culverts, bridges and other stream

crossings. It shall be the responsibility of the applicant to transfer this agreement to the new owner when the land associated with the watercourse alteration is transferred. A copy of all new agreements shall be provided to the floodplain administrator. Failure to transfer the agreement and provide a signed copy to the Floodplain Administrator shall subject the violator to the penalties set forth in Section 8.3 of this ordinance.

- F. The applicant must submit any maps, computations or other material required by the Federal Emergency Management Agency (FEMA) to revise the Flood Insurance Study and/or Flood Insurance Rate Maps, when notified by the floodplain Administrator, and must pay any fees or other costs assessed by FEMA for this purpose.

## **ARTICLE V - CRITERIA FOR BUILDING AND SITE PLAN APPROVAL**

### Section 5.1 General

Permits are required in order to determine whether all new development or substantial improvements are:

- A. Located in an identified Floodplain, Floodway or other flood hazard area.
- B. Designed (or modified) and adequately anchored to prevent flotation, collapse, or lateral movement of the structure resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy.
- C. Constructed with material and utility equipment resistant to flood damage as outlined in FEMA Technical Bulletin 2-93 (FIA-TB-2) or the most recent revision thereof.
- D. Constructed by methods and practices that minimize flood damage.
- E. Constructed with electrical, heating, ventilation, plumbing and air conditioning equipment and other service facilities that are designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding.

### Section 5.2 Basic Format

The basic format of the permit shall include the following:

- A. Name and address of applicant
- B. Name and address of owner of land on which proposed construction is to occur.
- C. Names, addresses, and valid WV license numbers of all contractors working at the building site, or affidavits stating that work is being performed by individuals exempt from contractor licensing as set forth in Title 28, Series 2, section 3.9 (b) of the West Virginia Code of state regulations or the most recent revision thereof.



- D. A description of site location sufficient to locate the project including tax map and parcel number.
- E. A standard site plan showing size and location of the proposed development as well as any existing buildings or structures. The site plan shall also show all adjacent roads and watercourses with direction of flow, the lowest adjacent grade to the proposed foundation and/or toe of fill, the Base Flood Elevation and the location of the floodway boundary when applicable.
- F. An acknowledgement that the applicant agrees to pay any and all fees associated with the permitting process as set forth in Section 7.9 hereof.
- G. An acknowledgement that the applicant agrees to allow community officials access to the development to inspect for compliance.
- H. The contract required by WV Code of State Regulations, Title 28, Series 4, and all addendums to the contract(s) shall be presented to the floodplain administrator for review within five (5) business days of contract signing. The community does not require and will not keep copies of the contracts or addendums. Failure to present contract or addendums for review shall void the permit. If a licensed contractor is not involved, or the work is of an aggregate value of less than ten thousand dollars including materials and labor, a brief written description of proposed work and the estimated value will suffice.

#### Section 5.3 Elevation and Flood Proofing Information

All applicants are encouraged to exceed the minimum elevation requirements contained herein. Flood insurance rates can be lowered significantly by increasing the elevation of the lowest floor above the freeboard height required by this ordinance.

Depending on the type of structure involved, the following information shall also be included in the application for work within the Floodplain Area:

- A. For structures to be elevated two feet above the Base Flood Elevation:
  - 1. A plan prepared by a registered professional engineer or licensed professional surveyor showing the size of the proposed structure and its relation to the lot where it is to be constructed, a determination of elevations of the Base Flood, existing ground, proposed finished ground, lowest floor, and the number and location of flood vents.
  - 2. Plans showing the method of elevating the proposed structure including details of proposed fills, pile structures, retaining walls, foundations, erosion protection measures, etc. When required by the Floodplain Administrator, a registered professional engineer or architect shall prepare these plans.
  - 3. Plans showing the methods used to protect utilities (including sewer, water, telephone, electric, gas, etc.) from flooding to two feet above the Base Flood Elevation at the building site.

4. During the course of construction, as soon as the basic elements of the lowest floor are in place and before further vertical construction, it is highly recommended that the applicant check for error by obtaining elevation data completed by a registered professional engineer or licensed professional surveyor certifying the height of the lowest floor. If a mistake in elevation has been made this is the best time to correct the error.
5. A Nonconversion Agreement shall be signed by the applicant whenever the community determines that the area below the first floor could be converted to a non-conforming use (generally areas below base flood elevation with ceilings higher than 5 feet). This agreement shall state:
  - (i) The area below Base Flood Elevation shall not be converted for use other than for parking, building access or for allowable storage as detailed in this ordinance.
  - (ii) The applicant agrees to notify prospective buyers of the existence of the non-conversion agreement. It shall be the responsibility of the applicant to transfer the agreement at closing to the new owner via notarized signature, a copy of all new agreements shall be provided to the Floodplain Administrator. Failure to transfer the agreement and provide a signed copy to the Floodplain Administrator shall subject the violator to the penalties set forth in Section 8.3 of this ordinance.
6. After the lowest floor is constructed, a finished construction Elevation Certificate containing elevations of the Base Flood, finished ground, lowest floor, and flood vents, certified by a registered professional engineer or licensed professional surveyor shall be submitted to the Putnam County Planning Commission. This certificate or report must confirm that the structure in question, together with attendant utilities is designed so that:
  - (i) The lowest floor of the structure (including basement) must be elevated at least two feet above the Base Flood Elevation.
  - (ii) Hydrostatic flood forces on exterior walls are equalized by allowing for automatic entry and exit of floodwaters. Designs for meeting this requirement must either be certified by a Registered Professional Engineer or Architect or meet or exceed the following minimum criteria:
    - a) A minimum of two openings (flood vents) having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding shall be provided.
    - b) The bottom of all openings shall be no higher than one foot above grade.
    - c) Openings may be equipped with screens, louvers, valves or other coverings or devices provided that they permit the automatic entry and exit of floodwaters.

B. For structures to be flood proofed to two feet above the Base Flood Elevation (nonresidential structures only):

All applicants are encouraged to exceed the minimum flood proofing requirements contained herein. Flood insurance rates can be lowered significantly by increasing the level of flood proofing above the height required by this ordinance. In order to obtain an “elevation credited” flood insurance rate on dry flood proofed buildings, flood proofing must extend at least one foot above the Base Flood Elevation.

1. Plans showing details of all flood proofing measures, prepared by a registered professional engineer, showing the size of the proposed structure and its relation to the lot where it is to be constructed.
2. A determination of elevations of the Base Flood, existing ground, proposed finished ground, lowest floor, and flood proofing limits; certified by a registered professional engineer or licensed professional surveyor.
3. A Flood proofing Certificate, FEMA 81-65, as revised by FEMA, shall be prepared by the registered professional engineer who prepared the plans in (1) above, stating the structure in question, together with attendant utility and sanitary facilities is designed so that:
  - (i) The structure is water tight with walls substantially impermeable to the passage of water from the lowest structural element to two feet above the Base Flood Elevation.
  - (ii) The structure will withstand the hydrostatic, hydrodynamic, buoyant, impact, and other forces resulting from the flood depths, velocities, pressures, and other factors associated with the Base Flood.

C. For structures constructed of flood resistant materials – used solely for parking of vehicles, or storage, (Appurtenant Structures only)

1. A site plan prepared by a licensed professional surveyor or others of demonstrated qualifications showing elevation of existing ground, proposed finished ground and lowest floor. The plan shall also show details of proposed flood resistant materials usage and the size of the proposed structure and its relation to the lot where it is to be constructed. The location of the floodway boundary shall be represented on the plan when a floodway is present on the site.
2. An elevation report or certificate, based on finished construction, must be prepared by a licensed professional surveyor or others of demonstrated qualifications. This certificate or report must confirm that the structure in question, together with attendant utilities is designed so that:
  - (i) Flood resistant materials as detailed in FEMA Technical Bulletin 2-93 (FIA-TB-2) are used in the construction of the structure from the lowest structural element to two feet above the Base Flood

Elevation and that all utilities are located at least two feet above the Base Flood Elevation.

- (ii) Hydrostatic flood forces on exterior walls are equalized by allowing for automatic entry and exit of floodwaters. Designs for meeting this requirement must either be certified by a Registered Professional Engineer or Architect or meet or exceed the following minimum criteria:
  - a) A minimum of two openings (flood vents) having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding shall be provided.
  - b) The bottom of all openings shall be no higher than one foot above grade.
  - c) Openings may be equipped with screens, louvers, valves or other coverings or devices provided that they permit the automatic entry and exit of floodwaters.
- 3. In addition, the applicant shall sign a Non-conversion Agreement and notify prospective buyers of the existence of the agreement. It shall be the responsibility of the applicant to transfer the Non-conversion Agreement to any new owner at closing via notarized signature. A signed copy of the transferred Non-conversion agreement shall be provided to the floodplain administrator. Failure to transfer the agreement and provide a signed copy to the Floodplain Administrator shall subject the violator to the penalties set forth in Section 8.3 of this ordinance.

#### Section 5.4 Site Plan Criteria

The owner or developer of any proposed development, including Subdivisions and Manufactured Home Parks, shall submit a preliminary site plan to the Floodplain Administrator that includes the following information:

- A. Name of registered professional engineer, licensed professional surveyor or other qualified person responsible for providing the information required in this section.
- B. A map showing the location of the proposed subdivision and/or development with respect to the county's floodplain areas, proposed lots sites, and fills. In addition, it is required that all subdivision proposals and other proposed new developments which are proposed to take place either fully or partially within the approximated floodplain (F4) and which are greater than three (3) lots or two (2) acres, whichever is the lesser, shall include base flood elevation data. If FEMA has completed a Flood Insurance Study (FIS), that data must be used to substantiate the base flood. Otherwise, the developer may submit data provided by an authoritative source, such as U.S. Army Corps of Engineers, U.S. Geological Survey, Natural Resources Conservation Service, state and local water resource departments, or technical data developed using detailed methodologies comparable to those contained in a Flood Insurance Study. This data shall be prepared and certified by a registered professional engineer,

who shall certify that the technical methods used correctly reflect currently accepted technical concepts.

- C. Where the subdivision and/or development lies partially or completely in the floodplain areas, the plan map shall include detailed information giving the location and elevation of proposed roads, public utilities and building sites. All such maps shall also show contours at intervals of two (2) or five (5) feet depending upon the slope of the land and identify accurately the boundaries of the floodplain areas.
- D. Where the subdivision lies partially in the floodplain area and all proposed development will take place on natural grade a significant vertical distance above the floodplain area, development of detailed Base Flood Elevation data may not be necessary. In these cases the site plan for the proposed development must clearly delineate the area to be developed and the location of the floodplain areas as depicted on the FEMA map. A registered professional engineer, licensed professional surveyor or others of demonstrated qualifications must certify the site plan.

## **ARTICLE VI - SPECIFIC REQUIREMENTS**

### **Section 6.1 Design and Construction Standards**

In order to prevent excessive damage to buildings, structures, and related utilities and facilities, the following restrictions apply to all development, subdivision proposals, manufactured home parks, new construction and to construction of substantial improvements, and the repair of substantial damage, to existing structures occurring in the Floodplain Area.

#### **A. Basements and Lowest Floors**

- 1. All new construction, relocation, substantial improvements, including repair of substantial damage, of residential structures must have the lowest floor, including basement, ductwork and utilities, elevated to two feet above the Base Flood Elevation.
- 2. All new construction, relocation, substantial improvements, including repair of substantial damage, of nonresidential structures must have the lowest floor, including basement, ductwork and utilities, elevated to two feet above the Base Flood Elevation; or, together with attendant utility and sanitary facilities, be designed so that the structure is water tight with walls substantially impermeable to the passage of water from the lowest structural element to two feet above the Base Flood Elevation.
- 3. For all new construction, relocation, substantial improvements, and repair of substantial damage, those fully enclosed areas below the lowest floor that are usable solely for parking of vehicles, building access or storage in an area other than a basement and which are subject to flooding shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for entry and exit of floodwaters. Designs for meeting this requirement must either be certified by a Registered Professional Engineer or meet or exceed the following minimum criteria:

- a) A minimum of two openings having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding shall be provided.
- b) The bottom of all openings shall be no higher than one foot above grade.
- c) Openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the automatic entry and exit of floodwaters.
- d) Openings should be located on at least two separate walls for insurance purposes.

## B. Manufactured Home Placement

Certain unique characteristics of manufactured homes installed in flood hazard areas pose an elevated risk of substantial damage to property.

1. Manufactured homes to be placed or substantially improved within flood hazard areas shall be installed in accordance with the following standards:
  - (i) The lowest floor, ductwork and utilities including HVAC/heat pump shall be elevated two feet above the Base Flood Elevation
  - (ii) Elevation shall be on reinforced piers on a permanent foundation or other foundation elements of at least equivalent strength engineered for use in a flood hazard area. Installation designs incorporating dry stacked block piers shall not be used in flood hazard areas.
  - (iii) All manufactured homes shall be securely anchored to an adequately anchored foundation system in compliance with the requirements of 42 West Virginia Code of State Regulations, Series 19, Sections 10.1, 10.2, and 10b as authorized by West Virginia Code § 21-9-4 or the most recent revisions thereof. The anchoring shall be adequate to resist flotation, collapse, or lateral movement. Methods of anchoring may include but are not limited to the over-the-top and frame ties, attached to permanent foundation elements. Ground anchors may not be adequate to satisfy flood specific anchoring requirements. This requirement is in addition to applicable State and local anchoring requirements for resisting wind forces.
  - (iv) Permanently attached rigid skirts and perimeter wall skirts of brick or block must have openings; this type of skirting can be collapsed by floodwaters and compromise supporting piers. The openings must be designed to automatically equalize hydrostatic flood forces by allowing for entry and exit of floodwaters. Designs for meeting this requirement must either be certified by a Registered Professional Engineer or meet or exceed the following minimum criteria:
    - a) A minimum of two openings having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding shall be provided.

- b) The bottom of all openings shall be no higher than one foot above grade.
  - c) Openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the automatic entry and exit of floodwaters.
- (v) Skirting that is not permanently attached and can break away from floodwaters is not required to have flood vents.
  - (vi) Any additions to a manufactured home shall be similarly anchored and vented.
2. A licensed WV Manufactured Home Installer shall perform a site inspection and certify in writing that the manufactured home has been installed to the standards set forth above.

### C. Appurtenant Structures

1. Except as provided in subsection 2 below, appurtenant structures shall be located out of the floodplain area or elevated to two feet above the Base Flood Elevation.
2. Where appurtenant structures not connected to the principal structure are to be located on sites below the Base Flood Elevation, the following flood damage reduction provisions apply:
  - a. Structures shall be no more than 600 square feet in size and valued at less than \$10,000.00.
  - b. Floors shall be at or above grade on at least one side.
  - c. Structures shall be located, oriented and constructed to minimize flood damage.
  - d. Structures shall be designed (or modified) and adequately anchored to prevent flotation, collapse, or lateral movement of the structure resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy.
  - e. Flood resistant materials as detailed in FEMA Technical Bulletin 2-93 (FIA-TB-2) shall be used in the construction of the structure from the lowest structural element to two feet above the Base Flood Elevation.
  - f. Machinery, electric devices or appliances, and all utilities shall be located at least two feet above the Base Flood Elevation.
  - g. The venting requirements contained in Section 6.1 (A-3) are applicable and shall be strictly adhered to.
  - h. Use of the structure shall be restricted to parking or limited storage.
3. A Nonconversion Agreement shall be signed by the applicant stating that

the use of the appurtenant structure or detached or attached garage shall not be changed from the use permitted, acknowledging that the structure may be subject to greater flood risk and that higher flood insurance premiums may be possible, and that a change in use may require full compliance with this ordinance. The applicant agrees to notify prospective buyers of the existence of this agreement. It shall be the responsibility of the applicant to transfer the agreement at closing to the new owner via notarized signature, a copy of all new agreements shall be provided to the floodplain administrator. Failure to transfer the agreement and provide a signed copy to the Floodplain Administrator shall subject the violator to the penalties set forth in Section 8.3 of this ordinance.

#### D. Recreational Vehicle Placement

1. Recreational vehicles to be placed within any floodplain area shall either:
  - a. Be on site for fewer than 180 consecutive days or,
  - b. Be fully licensed and ready for highway use. A recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect utilities and security devices, and has no permanently attached additions. Or,
  - c. Be installed in accordance with the Manufactured Home Placement requirements and all other flood reduction requirements contained in this ordinance.

#### E. Fill

The Putnam County Planning Commission officially recognizes the beneficial functions the floodplain serves in storage and transportation of water during floods. No fill shall be permitted in the floodway. Placement of fill in the floodplain area is discouraged and should be minimized. All fill placed in the floodplain area shall meet or exceed the following standards:

1. Fill shall be used in the floodplain area only to the extent to which it does not adversely affect adjacent properties. The Putnam County Planning Commission shall require a plan showing original and proposed contours at intervals no greater than 2 vertical feet and may require the applicant to demonstrate through engineering reports that proposed fill would not adversely affect adjacent properties. When required, hydrologic and hydraulic analyses shall be undertaken only by professional engineers who shall certify that the technical methods used correctly reflect currently accepted technical concepts. The resultant study shall include a cover letter, signed and sealed by the responsible professional, providing a statement of findings in basic terms. In addition, studies, analyses, computations, etc. shall be submitted in sufficient detail to allow a thorough technical review by the Putnam County Planning Commission. During permit review the community shall consider the following issues that have the potential to cause adverse impact to adjacent properties:
  - a. Unacceptable increases in flood heights.
  - b. Blocking drainage from adjacent property.
  - c. Deflection of floodwaters onto adjacent existing structures.



- d. Increases to stream velocity initiating or exacerbating erosion problems.
  - e. Other unique site conditions may be considered when determining whether fill will cause adverse impact to adjacent property including, but not limited to, subsidence areas, karst topography, stream blockages, and steep topography adjacent to the channel.
2. Fill shall be used only to the extent to which it does not adversely affect the capacity of channels or floodways of any tributary to the main stream, drainage ditch, or any other drainage facility or system.
3. Filled site must be contoured to drain properly (avoid ponding)
4. Fill shall extend beyond a structure for a sufficient distance to provide acceptable access. For residential structures, fill shall extend laterally fifteen (15) feet beyond the building line from all points before the start of sloping required in following subsection. For nonresidential structures, fill shall be placed to provide access acceptable for intended use. At grade access, with fill extending laterally fifteen (15) feet beyond the building line shall be provided to a minimum of twenty-five (25) percent of the perimeter of a nonresidential structure.
5. Fill shall consist of soil or rock material only. Sanitary landfills shall not be permitted, no trash or woody debris shall be buried on site.
6. Fill material shall be compacted to provide the necessary stability and resistance to erosion, scouring or settling. Fill compaction standards must be appropriate to proposed post fill use, particular attention is necessary when fill is being used to elevate a structure.
7. Fill slopes shall be no steeper than one (1) vertical on two (2) horizontal, unless substantiating data justifying steeper slopes are submitted to and approved by the County Engineer.
8. Fill site and fill must be protected from erosion.
  - a. Fill slopes exposed to flood waters with expected velocities during the occurrence of the base flood of five feet per second or less must be protected from erosion by covering them with grass, vines, weeds, or similar vegetative undergrowth.
  - b. Fill slopes exposed to flood waters with expected velocities during the occurrence of the base flood of greater than five feet per second must be protected from erosion by armoring them with stone or rock slope protection.
9. The applicant must submit any maps, computations or other material required by the Federal Emergency Management Agency (FEMA) to revise the Flood Insurance Study and/or Flood Insurance Rate Maps, when notified by the Floodplain Administrator, and must pay any fees or other costs assessed by FEMA for this purpose.

## F. Placement of Structures

1. All buildings and structures shall be constructed and placed on the lot so as to offer the minimum obstruction to the flow of water and shall be designed to have a minimum obstruction effect upon the flow and height of floodwater.
  - i. Whenever possible, structures shall be constructed with the longitudinal axis parallel to the direction of flood flow and,
  - ii. So far as practicable, structures shall be placed approximately on the same flood-flow lines as those of adjoining structures.

## G. Anchoring

1. All buildings and structures shall be firmly anchored in accordance with accepted engineering practices to prevent flotation, collapse, and lateral movement, thus reducing the threat to life and property and decreasing the possibility of the blockage of bridge openings and other restricted sections of the watercourse.
2. All air ducts, large pipes, and storage tanks located at or below the Base Flood Elevation shall be firmly anchored to resist flotation.

## H. Storage

1. No materials that are buoyant, flammable, explosive, or in times of flooding could be injurious to human, animal or plant life, shall be stored below Base Flood Elevation.
2. Storage of other material or equipment may be allowed if not subject to major damage by floods and firmly anchored to prevent flotation or readily removable from the area within the time available after flood warning.
3. Due to the potential of masking the natural elevation and making it more difficult to enforce this ordinance, material that resembles “fill” material shall not be considered “storage” material for purposes of this subsection.

## I. Utility and Facility Requirements

1. All new or replacement water systems whether public or private, shall be designed to minimize or eliminate infiltration of floodwaters into the systems.
2. All new or replacement sanitary disposal systems, whether public or private, shall be designed to minimize or eliminate infiltration of floodwaters into the systems and discharges from the systems into floodwaters.

3. All other new or replacement public and/or private utilities and facilities shall be located and constructed to minimize or eliminate flood damage.
4. Onsite waste disposal systems shall be located to avoid impairment to them or contamination from them during flooding.

J. Drainage

Adequate drainage shall be provided to reduce exposure to flood hazard.

K. Backflow Preventers

Back flow prevention valves should be used for all enclosed structures with sewage or drainage facilities located in the floodplain.

## **ARTICLE VII - ADMINISTRATION**

### Designation of Floodplain Administrator

The Putnam County Planning Commission Director is hereby appointed as Floodplain Administrator to administer and implement this local law by granting or denying floodplain development permits in accordance with its provisions.

#### Section 7.1 Development Permits and Site Plan Approvals Required

It shall be unlawful for any contractor, person, partnership, business, or corporation to undertake or cause to be undertaken, any development or new construction, substantial improvement, repair of substantial damage, the placement or relocation of any structure (including manufactured homes) within the unincorporated areas of Putnam County, unless a permit application and standard site plan has been completed, and a permit has been obtained from the Floodplain Administrator. In addition, where land that is either partially or fully in the regulatory floodplain is to be subdivided, utilized for a manufactured home park or subdivision or otherwise developed, a detailed site plan must be submitted to, and approved by, the Floodplain Administrator prior to any development.

#### Section 7.2 Approval of Permits and Plans

1. The Floodplain Administrator shall review, or shall cause to be reviewed; all permit applications and plans in order to determine whether proposed building sites are reasonably safe from flooding.
2. All permits and plans shall be approved only after it has been determined that the proposed work to be undertaken will be in conformance with the requirements of the state and all other applicable codes and ordinances.
3. The Floodplain Administrator shall not issue a permit to any person who does not possess a valid contractor's license when a contractor's license is required by West Virginia State Code §21-11-10.
4. The Floodplain Administrator, before issuance of the permit, shall require the applicant to furnish satisfactory proof that such person is duly licensed as a

contractor under the provisions of West Virginia State Code. If the applicant is not licensed a written affidavit that such person is not subject to licensure as a contractor or subcontractor as defined in §21-11-3 shall be provided to the Floodplain Administrator and placed in the permit file.

5. The Floodplain Administrator shall require copies of all necessary permits from those governmental agencies from which Federal or State Law requires approval.
6. The Floodplain Administrator shall provide a copy of all permits to the County Assessor as required by West Virginia State Code 11-3-3A.
7. The Floodplain Administrator shall provide a copy of all permits for new structures to the County E-911 addressing coordinator.
8. The County E-911 addressing coordinator shall provide a copy of all requests for addresses for new structures to the County Floodplain Administrator.
9. The Putnam County Commission shall provide sufficient space to allow the Floodplain Administrator to keep on file in perpetuity, in a location safe from natural hazards, all information collected during the course of the administration of this ordinance.

#### Section 7.3 Application Procedures

Application for a permit and/or site plan approvals shall be made, in writing, on the forms supplied by the Putnam County Planning Commission, and shall include all information stipulated under Article V of this ordinance.

#### Section 7.4 Changes

After the issuance of a permit or site plan approval by the Floodplain Administrator, no changes of any kind shall be made to the application, permit, or any of the plans, specification or other documents submitted with the application without the written consent or approval of the Floodplain Administrator.

#### Section 7.5 Permit Placards

- A. The Floodplain Administrator shall issue a permit placard, which shall be prominently displayed on the premises during the time construction is in progress. This placard shall show the number of the permit, the date of its issuance and be signed by the Floodplain Administrator.
- B. In areas of flood hazard it shall be unlawful to inspect and approve or install a temporary electrical utility connection to any building or premises, or both, or part thereof hereafter created, erected or rebuilt until a placard has been issued by the Local Floodplain Administrator indicating that the development has applied for a permit and agreed to the requirements of this local law or, in the case of development occurring outside of the identified flood hazard area, a Certificate of Compliance has been issued.

## Section 7.6 Start of Construction

Work on the proposed development, as defined as the “start of construction” definition, shall begin within 180 days after the date of issuance of the permit or the permit shall expire unless a time extension is granted, in writing, by the Floodplain Administrator. All work on the proposed development must be completed within 18 months of permit issuance, at which time the permit shall expire, unless a time extension is granted in writing by the Planning Commission. The request for a time extension shall be in writing and shall state the reasons for the extension. When considering an extension, the Planning Commission shall consider the following criteria:

- 1) Has the developer diligently pursued the completion of the proposed development during the 18 months?
- 2) Will the granting of the extension be detrimental to public safety, health, or welfare or injurious to other property?

## Section 7.7 Stop Work Orders, Inspections and Revocations

### A. Stop-Work Orders

1. The Floodplain Administrator shall issue, or cause to be issued, a “Stop Work Order Notice” for any development found ongoing without having obtained a permit. Disregard of a stop work order shall subject the violator to the penalties described in Section 8.3 of this local law.
2. The Floodplain Administrator shall issue, or cause to be issued, a “Stop Work Order Notice” for any development found non-compliant with the provisions of this law and/or the conditions of the permit. Disregard of a stop work order shall subject the violator to the penalties described in Section 8.3 of this local law.

### B. Inspections and Revocations

1. During the construction period, the Floodplain Administrator or other authorized official may inspect the premises to determine that the work is progressing in compliance with the information provided on the permit application and with all applicable laws and ordinances.
2. If the Floodplain Administrator discovers that the work does not comply with the permit application or any applicable laws and ordinances or that there has been false statement or misrepresentation by any applicant, the Floodplain Administrator shall issue a “Stop Work Order Notice” revoke the permit and request a temporary injunction.
3. The Floodplain Administrator or other authorized official may inspect any development covered by this or previous ordinance to determine whether any portion of the development has been altered to be in non-compliance with the requirements of this ordinance.

## Section 7.8 Certificate of Compliance

- A. In areas of flood hazard it shall be unlawful to occupy, or to permit the use or occupancy, of any building or premises, or both, or part thereof hereafter created, erected, installed, changed, converted or wholly or partly altered or enlarged in its use or structure until a certificate of compliance has been issued by the Local Floodplain Administrator stating that the building or land conforms to the requirements of this local law. Occupying or using a building or premises in violation of this section shall subject the violator to the penalties described in Section 8.3 of this local law.
- B. In areas of flood hazard it shall be unlawful to inspect and approve a permanent utility connection to any building or premises, or both, or part thereof hereafter created, erected, installed or rebuilt until the inspector is in possession of a copy of the certificate of compliance issued by the Local Floodplain Administrator stating that the particular development being inspected conforms to the requirements of this local law. Inspection and approval of utilities in violation of this section shall subject the violator to the penalties described in Section 8.3 of this local law.
- C. In areas of flood hazard it shall be unlawful to install a permanent utility connection to any building or premises, or both, or part thereof hereafter created, erected, installed or rebuilt until a certificate of compliance has been issued by the Local Floodplain Administrator stating that the development conforms to the requirements of this local law. Installation of utilities in violation of this section shall subject the violator to the penalties described in Section 8.3 of this local law.
- D. A certificate of compliance shall be issued by the Local Administrator upon satisfactory completion of all development in areas of special flood hazard.
- E. Issuance of the certificate shall be based upon the inspections conducted as prescribed in this ordinance or local administrative procedures, and any finished construction elevation certificate, hydraulic data, flood proofing certificate, or encroachment analyses which may have been required as a condition of permit approval.

## Section 7.9 Fees

- A. A Floodplain Determination fee of \$30.00, payable to the “Putnam County Commission” shall be assessed on all proposed development.
- B. In addition to the Floodplain Determination fee, the following fees are assessed:

<u>DEVELOPMENT OUTSIDE OF A FLOOD HAZARD AREA</u>	<u>FEE</u>
Grading and Filling	\$30.00/acre or part thereof
Bridge, Culvert, Stream Relocation and other development not specified	\$30.00*
Commercial, Industrial, Multi-Family, Leased Community	\$1.00/per thousand of construction costs*
Site Plans and Engineering Reports for but not limited to Commercial, Industrial, Multi-Family, Leased Community (additional fee)	\$400.00

<u>DEVELOPMENT IN A FLOOD HAZARD AREA</u>	<u>FEE</u>
Single Family and Duplex Residential Dwelling	\$1.00/per thousand of construction costs*
Manufactured Home	\$1.00/per thousand of construction costs*
Substantial Addition to Single Family and Duplex Residential Dwelling	\$1.00/per thousand of construction costs*
Grading and Filling	\$30.00/acre or part thereof*
Bridge, Culvert, Stream Relocation and all other uses not specified	\$30.00*
Commercial, Industrial, Multi-Family, Leased Community	\$1.00/per thousand of construction costs*
Addition or Substantial Addition to Commercial, Industrial, Multi-Family, Leased Community	\$1.00/per thousand of construction costs*

\*Site Plans and Engineering Reports required  
Site Plans and Engineering Reports for but not limited to  
Commercial, Industrial, Multi-Family, Leased Community,  
Grading, Filling, Bridge, Culvert, Stream Relocation (additional fee)      \$400.00

Floodway Development Reviews (additional fee)      \$400.00

Appeal      \$200.00  
If the decision of the Floodplain Administrator is reversed,  
\$100 will be refunded.

*\*Construction costs shall include labor and materials.  
Minimum fee shall be \$30.00*

- C. In addition, the applicant shall be responsible for reimbursing the Putnam County Planning Commission for any additional costs for services necessary for review and/or inspection of proposed development. Services include, but are not limited to, professional engineering and surveying. The Floodplain Administrator may require a deposit towards these additional costs. Additional costs may include reimbursement for contracted services.
- D. Due to the increased cost of processing, when any work for which a permit is required by this ordinance is started or proceeded with prior to obtaining a permit the fees above specified shall be doubled. Payment of the doubled fee shall not relieve any person from complying fully with the requirements of this ordinance in the execution of the work or from other penalties prescribed herein.

## **ARTICLE VIII - APPEALS AND PENALTIES**

### **Section 8.1 Appeals**

Whenever any person is aggrieved by a decision of the Floodplain Administrator with respect to the provision of this ordinance, it is the right of that person to appeal to the Putnam County Planning Commission. Such appeal must be filed with the Planning Commission, in writing and submitted to the Office of Planning and Infrastructure, within thirty (30) days after notification of the decision. Upon receipt of such appeal, the Planning Commission shall set a time and place not less than ten (10) nor more than sixty (60) days for the purpose of hearing the appeal. Notice of the time and place of the hearing shall be given to all parties at which time they may appear and be heard.

Appeals regarding any decision made by the Planning Commission in the administration of this Ordinance shall be by certiorari procedure as set forth in Section 8A-9 of the West Virginia Code.

Any person or persons jointly or severally aggrieved by any decision or order of the Planning Commission may present to the Circuit Court of Putnam County a petition duly verified, setting forth that such decision or order is illegal in whole or in part, and specifying the grounds of the alleged illegality. The petition shall be presented to the Court within thirty (30) days after the date of the Commission's decision.

### **Section 8.2 Appeal/Variance Review Criteria**

- A. All appeals contesting only the permit fee, the cumulative substantial damage requirement, or the freeboard requirements may be handled at the discretion of the Putnam County Planning Commission.



- B. If compliance with any of the requirements of this Ordinance would result in an exceptional hardship to a prospective builder, developer or landowner, the Putnam County Planning Commission may, upon request, grant relief from the strict application of the requirements. All decisions on appeals or variances to all other provisions of this ordinance shall adhere to the following criteria:
1. Affirmative decisions shall only be issued by the Planning Commission upon (i) a showing of good and sufficient cause, (ii) a determination that failure to grant the appeal/variance would result in exceptional hardship to the applicant, and (iii) a determination that the granting of an appeal/variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisances, cause fraud on or victimization of the public or conflict with existing locals laws or ordinance.
  2. An affirmative decision shall be issued only upon determination that it is the minimum necessary, considering the Special Flood Hazard Area and other flood hazards, to afford relief. Financial hardship, as a sole criterion, shall not be considered sufficient justification to grant an appeal/variance.
  3. An affirmative decision granting a Floodplain appeal/variance shall be issued for the repair or rehabilitation of historic structures upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and the appeal/variance is the minimum necessary to preserve the historic character and design of the structure.
  4. The Putnam County Planning Commission shall notify the applicant in writing signed by the President of the Planning Commission or designee that (i) the issuance of a decision to allow construction of a structure below the Base Flood Elevation will result in increased premium rates for flood insurance, (ii) such construction below the Base Flood Elevation increases risk to life and property. Such notifications shall be maintained with a record of all decisions as required as required in this Ordinance; and
  5. The Putnam County Planning Commission shall (i) maintain a record of all decisions including justification for their issuance, and (ii) report such decisions issued in its biannual report to the Federal Emergency Management Agency.
  6. An affirmative decision shall not be granted for any construction, development, use or activity within any floodway area that would cause any increase in the Base Flood Elevation.

### Section 8.3 Penalties

Any person who fails to comply with any or all of the requirements or provisions of this ordinance or direction of the Floodplain Administrator or any other authorized employee of the community shall be unlawful and shall be referred to the Prosecuting Attorney who shall expeditiously prosecute all such violators. A

violator shall, upon conviction, pay a fine to the Putnam County Commission of not less than fifty dollars (\$50.00) or more than five hundred dollars (\$500.00) plus cost of prosecution. In default of such payment such person shall be imprisoned for a period not to exceed 10 days. Each day during which any violation of this ordinance continues shall constitute a separate offense. In addition to the above penalties, all other actions are hereby reserved including an action in equity for the proper enforcement of this ordinance. The imposition of a fine or penalty for any violation of, or non-compliance with, this ordinance shall not excuse the violation or non-compliance with the ordinance or permit it to continue; and all such persons shall be required to correct or remedy such violations or non-compliance within a reasonable time. Any structure constructed, reconstructed, enlarged, altered or relocated in non-compliance with this ordinance may be declared by the Putnam County Planning Commission to be a public nuisance and abatable as such.

## **ARTICLE IX – GOVERNMENT ACTIONS**

### Section 9.1 – Municipal Annexation

- A. The County floodplain ordinance in effect on the date of annexation shall remain in effect and shall be enforced by the municipality for all annexed areas until the municipality adopts and enforces an ordinance which meets the requirements for participation in the National Flood Insurance Program.
- B. Municipalities with existing floodplain ordinances shall pass a resolution acknowledging and accepting responsibility for enforcing floodplain ordinance standards prior to annexation of any area containing identified flood hazards.
- C. All plats or maps of annexation shall show the floodplain boundaries, Base Flood Elevation and location of the floodway where determined.
- D. In accordance with the Code of Federal Regulations, Title 44 Subpart (B) Section 59.22 (a) (9) (v) all NFIP participating communities must notify the Federal Insurance Administration in writing whenever the boundaries of the community have been modified by annexation or the community has otherwise assumed or no longer has authority to adopt and enforce flood plain management regulations for a particular area. In order that all Flood Insurance Rate Maps accurately represent the community's boundaries, a copy of a map of the community suitable for reproduction, clearly delineating the new corporate limits or new area for which the community has assumed or relinquished flood plain management regulatory authority must be included with the notification.
- E. NFIP participating communities must notify the State Coordinating Office in writing whenever the boundaries of the community have been modified by annexation or the community has otherwise assumed or no longer has authority to adopt and enforce flood plain management regulations for a particular area. A copy of a map of the community suitable for reproduction, clearly delineating the new corporate limits or new area for which the community has assumed or relinquished flood plain management regulatory authority must be included with the notification.

Section 9.2 – Permits for Government Entities.

- A. Unless specifically exempted by law, all public utilities and Municipal, County, State and Federal entities are required to comply with this ordinance and obtain all necessary permits. Any entity claiming to be exempt from the requirements of this ordinance must provide a written statement setting forth the rationale for exemption. In addition the entity claiming exemption shall provide copies of all relevant legal documentation demonstrating the exemption.

**ARTICLE X - SEVERABILITY AND MUNICIPAL LIABILITY**

Section 10.1 Severability

If any section, subsection, paragraph, sentence, clause, or phrase of this ordinance shall be declared invalid for any reason whatever, such decision shall not affect the remaining portions of this ordinance which shall remain in full force and effect and for this purpose the provisions of this ordinance are hereby declared to be severable.

Section 10.2 Liability

The granting of a permit or approval of a subdivision or development plan in an identified flood-prone area, shall not constitute a representation, guarantee, or warranty of any kind by the Putnam County Commission and the Putnam County Planning Commission, or by any official or employee thereof of the practicability or safety of the proposed use, and shall create no liability upon the Putnam County Commission and the Putnam County Planning Commission. All applicants proposing development in or near a flood hazard area are urged to locate development as far away from, and as high above, all flooding sources as possible.

**ARTICLE XI - ENACTMENT**

ENTERED this 14th day of April, 2015.

PUTNAM COUNTY COMMISSION  
OF PUTNAM COUNTY, WEST VIRGINIA

---

R, Andrew Skidmore, President

---

Stephen A. Andes, Commissioner

---

R. Joseph Haynes, Commissioner